

# Product datasheet

Specifications



APC Back-UPS, 1100VA, Tower, 230V, 5 India 3-pin 6A Outlets, AVR, W/O Auto Shutdown Software

BX1100I-IN

## Overview

Lead time Usually in Stock

## Main

Main Input Voltage	230 V
Rated power in W	660 W
Rated power in VA	1100 VA
Product or component type	Uninterruptible power supply (UPS)
Input Connection Type	India 3-pin 6A 6 A
Cable length	1.2 m
Number of cables	1
Battery type	Lead-acid battery

## Batteries & Runtime

Efficiency	<a href="#">View Efficiency Graph</a>
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	6 h
Number of battery replacement quantity	2
Battery voltage	24 V
Battery graph comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several v
Replacement battery	<a href="#">APCRBCV210</a>

## General

Provided equipment	1.2 m
Max runtime	0.2 min
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

## Physical

Colour	Black
Height	297 mm
Width	495 mm
Depth	235 mm
Net weight	9.2 kg
mounting mode	Not rack-mountable
Two post mountable	0

## Input

Network frequency	40...70 Hz auto-sensing
Plug standard	India 3-pin 6A
Input voltage limits	140...300 V

## Output

Maximum configurable power in W	660 W
Output frequency	Sync to mains
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Full load runtime	660 W
Maximum configurable power in VA	1100 VA
Transfer time	10 ms typical : 12 ms maximum

## Conformance

Product certifications	BIS
------------------------	-----

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...3000 m
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0...15000 m
acoustic level	45 dBA

## Communications & Management

Control panel	LED status display with load and battery bar-graphs and on line : on battery : replace battery : and overload indicators
---------------	--

## Surge Protection and Filtering

Surge energy rate	255 J
-------------------	-------

## Packing Units

Unit Type of Package 1	PCE
------------------------	-----

---

<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	19.0 cm
<b>Package 1 Width</b>	14.0 cm
<b>Package 1 Length</b>	39.0 cm
<b>Package 1 Weight</b>	8.2 kg
<b>SCC14</b>	10731304743511

---

## **Contractual warranty**

---

**Warranty** 2 years repair or replace

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Rohs Exemption Information Yes

## Certifications & Standards

**Eu Rohs Directive** Compliant with Exemptions

**China Rohs Regulation** [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information

**Environmental Disclosure** [Product Environmental Profile](#)

**Circularity Profile** [End of Life Information](#)