

Product datasheet

Specifications



APC Easy UPS On-Line, 15kVA/15kW, Rackmount 3U, 230V, 1x Hard wire 3-wire(1P+N+E) outlet, Intelligent Card Slot, No battery, W/O rail kit

SRV15KUXI-IN

Overview

Presentation High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.

Lead time Usually in Stock

Main

Main Input Voltage 230 V AC
415 V AC

Product or component type Uninterruptible power supply (UPS)

Other Input Voltage 220 V
230 V
415 V

Main Output Voltage 230 V

Other Output Voltage 220 V
240 V

Rated power in W 15000 W

Rated power in VA 15000 VA

Output connector type Hard wire 3-wire (1P + N + E) 1

number of rack unit 3U

Provided equipment 1 USB cable
1 RS-232 configuration cable
1 rack mounting brackets
1 stabilization/wall mounting feet
1 battery cable
6 jumper bar
user manual

Range of product Easy UPS On-Line

Batteries & Runtime

Efficiency [View Efficiency Graph](#)

Battery type External battery system

Battery voltage +/- 120 V

Number of battery filled slots 0

Number of battery free slots 0

Battery charger power 2340 W rated

General

| | |
|-----------|----|
| Redundant | No |
|-----------|----|

Physical

| | |
|---------------------|-----------------------|
| Colour | Black (RAL 7010) |
| Height | 13.0 cm |
| Width | 43.8 cm |
| Depth | 68.9 cm |
| Net weight | 29 kg |
| mounting location | Front |
| Mounting preference | No preference |
| mounting mode | Rack-mounted with kit |
| USB compatible | Yes |
| mounting position | Horizontal |

Input

| | |
|----------------------------|--|
| Input voltage limits | 110...300 V half load 176...300 V full load |
| Number of input connectors | 1 hard wire 3-wire (1P + N + E) 1 hard wire 5-wire (3P + N + E) |
| Network frequency | 40...70 Hz auto sensing |

Output

| | |
|----------------------------------|--|
| Maximum configurable power in VA | 15000 VA |
| Maximum configurable power in W | 15000 W |
| Output frequency | 50/60 Hz +/- 3 Hz sync to mains |
| Harmonic distortion | 2 % |
| UPS type | Double conversion online |
| Wave type | Sine wave |
| Efficiency | 95 % (full load) |
| Additional information | Configurable for 220 : 230 or 240 nominal output voltage |
| Bypass type | Internal bypass (automatic and manual) |
| Crest factor | 3 : 1 |

Conformance

| | |
|------------------------|----|
| Product certifications | CE |
|------------------------|----|

Environmental

| | |
|---------------------------------------|-------------------------|
| Ambient air temperature for operation | 0...40 °C |
| Relative humidity | 0...95 % non-condensing |
| Operating altitude | 0...3000 m |
| Ambient air temperature for storage | -20...60 °C |
| Storage Relative Humidity | 0...95 % non-condensing |
| Storage altitude | 0...15000 m |

| | |
|-------------------------|------------|
| acoustic level | 65 dBA |
| Heat dissipation | 2503 Btu/h |
| IP degree of protection | IP20 |

Communications & Management

| | |
|---------------------|--|
| Alarm | Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm |
| Emergency power off | Yes |
| Control panel | Multifunction LCD status and control console |

Surge Protection and Filtering

| | |
|-------------------|-------|
| Surge energy rate | 600 J |
|-------------------|-------|

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 25 cm |
| Package 1 Width | 87 cm |
| Package 1 Length | 58 cm |
| Package 1 Weight | 35.9 kg |

Contractual warranty

| | |
|----------|---------------------------|
| Warranty | 2 years repair or replace |
|----------|---------------------------|

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Reach Free Of Svhc

Mercury Free

Rohs Exemption Information [Yes](#)

Certifications & Standards

Eu Rohs Directive [Compliant](#)
[EU RoHS Declaration](#)

China Rohs Regulation [China RoHS declaration](#)
Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile [End of Life Information](#)