

Product datasheet

Specifications



APC Easy UPS On-Line, 1000VA,
Rackmount 2U, 230V, 4x India
outlets, Intelligent Card Slot, No
battery, W/O rail kit

SRV1KUXI-IN

Overview

| | |
|---------------------|---|
| Presentation | High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions. |
| Lead time | Usually in Stock |

Main

| | |
|----------------------------------|--|
| Main Input Voltage | 230 V |
| Product or component type | Uninterruptible power supply (UPS) |
| Other Input Voltage | 220 V 240 V |
| Main Output Voltage | 230 V |
| Other Output Voltage | 220 V 240 V |
| Rated power in W | 800 W |
| Rated power in VA | 1000 VA |
| Input Connection Type | IEC 60320 C14 |
| output connection type | 4 India 3-pin 6A |
| number of rack unit | 2U |
| Cable length | 1.5 m |
| Number of cables | 1 |
| Provided equipment | 1 IEC 60320 C13 to India 3-pin 6A power cable 1 USB cable 1 RS-232 configuration cable 1 rack mounting brackets 1 stabilization/wall mounting feet 1 battery cable user manual |
| Range of product | Easy UPS On-Line |

Batteries & Runtime

| | |
|---------------------------------------|---------------------------------------|
| Efficiency | View Efficiency Graph |
| Battery type | External battery system |
| Battery voltage | 24 V |
| Number of battery filled slots | 0 |
| Number of battery free slots | 0 |
| Battery charger power | 235 W rated |

General

| | |
|-------------------------------------|----|
| Number of power module filled slots | 0 |
| Number of power module free slots | 0 |
| Redundant | No |

Physical

| | |
|---------------------|-----------------------|
| Colour | Black (RAL 7010) |
| Height | 8.6 cm |
| Width | 43.8 cm |
| Depth | 33.2 cm |
| Net weight | 7.2 kg |
| mounting location | Front |
| Mounting preference | No preference |
| mounting mode | Rack-mounted with kit |
| USB compatible | Yes |
| mounting position | Horizontal |

Input

| | |
|-----------------------|--|
| Input voltage limits | 110...280 V half load 160...280 V full load |
| Input protection type | Circuit breaker |
| Network frequency | 40...70 Hz auto sensing |

Output

| | |
|----------------------------------|--|
| Maximum configurable power in VA | 1000 VA |
| Maximum configurable power in W | 800 W |
| Output frequency | 50/60 Hz +/- 3 Hz sync to mains |
| Harmonic distortion | 3 % |
| UPS type | Double conversion online |
| Wave type | Sine wave |
| Efficiency | 88 % (full load) |
| Additional information | Configurable for 220 : 230 or 240 nominal output voltage |
| Bypass type | Internal bypass (automatic and manual) |
| Crest factor | 3 : 1 |

Conformance

| | |
|------------------------|-----|
| Product certifications | BIS |
|------------------------|-----|

Environmental

| | |
|---------------------------------------|-------------------------|
| Ambient air temperature for operation | 0...40 °C |
| Relative humidity | 0...95 % non-condensing |
| Operating altitude | 0...3000 m |

| | |
|-------------------------------------|-------------------------|
| Ambient air temperature for storage | -20...60 °C |
| Storage Relative Humidity | 0...95 % non-condensing |
| Storage altitude | 0...15000 m |
| acoustic level | 50 dBA |
| Heat dissipation | 372 Btu/h |
| IP degree of protection | IP20 |

Communications & Management

| | |
|---------------------|--|
| Alarm | Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm |
| Emergency power off | Yes |
| Control panel | Multifunction LCD status and control console |

Surge Protection and Filtering

| | |
|-------------------|-------|
| Surge energy rate | 600 J |
|-------------------|-------|

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 24 cm |
| Package 1 Width | 55 cm |
| Package 1 Length | 50 cm |
| Package 1 Weight | 10.3 kg |

Contractual warranty

| | |
|----------|---------------------------|
| Warranty | 2 years repair or replace |
|----------|---------------------------|

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Mercury Free

RoHS Exemption Information [Yes](#)

Certifications & Standards

Eu RoHS Directive Compliant
[EU RoHS Declaration](#)

China RoHS Regulation [China RoHS declaration](#)
Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile [End of Life Information](#)