

# Product datasheet

Specifications



APC Easy UPS On-Line, 3kVA, Rackmount 2U, 230V, 3x India + 1x Hard wire 3-wire(1P+N+E) outlets, Intelligent Card Slot, No battery, W/O rail kit

SRV3KUXI-IN

## Overview

**Presentation** High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.

**Lead time** Usually in Stock

## Main

**Main Input Voltage** 230 V

**Product or component type** Uninterruptible power supply (UPS)

**Other Input Voltage** 220 V  
240 V

**Main Output Voltage** 230 V

**Other Output Voltage** 220 V  
240 V

**Rated power in W** 2400 W

**Rated power in VA** 3000 VA

**output connection type** 3 India 3-pin 6A

**Output connector type** Hard wire 3-wire (1P + N + E) 1

**number of rack unit** 2U

**Provided equipment** 1 USB cable  
1 RS-232 configuration cable  
1 rack mounting brackets  
1 stabilization/wall mounting feet  
1 battery cable  
user manual

**Range of product** Easy UPS On-Line

## Batteries & Runtime

**Efficiency** [View Efficiency Graph](#)

**Battery type** External battery system

**Battery voltage** 72 V

**Number of battery filled slots** 0

**Number of battery free slots** 0

**Battery charger power** 700 W rated

## General

**Number of power module filled slots** 0

Number of power module free slots	0
Redundant	No

## Physical

Colour	Black (RAL 7010)
Height	8.6 cm
Width	43.8 cm
Depth	46.2 cm
Net weight	10.1 kg
mounting location	Front
Mounting preference	No preference
mounting mode	Rack-mounted with kit
USB compatible	Yes
mounting position	Horizontal

## Input

Input voltage limits	110...280 V half load 160...280 V full load
Number of input connectors	1 hard wire 3-wire (1P + N + E)
Input protection type	Circuit breaker
Network frequency	40...70 Hz auto sensing

## Output

Maximum configurable power in VA	3000 VA
Maximum configurable power in W	2400 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Harmonic distortion	3 %
UPS type	Double conversion online
Wave type	Sine wave
Efficiency	90 % (full load)
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Bypass type	Internal bypass (automatic and manual)
Crest factor	3 : 1

## Conformance

Product certifications	BIS
------------------------	-----

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-20...60 °C

<b>Storage Relative Humidity</b>	0...95 % non-condensing
<b>Storage altitude</b>	0...15000 m
<b>acoustic level</b>	50 dBA
<b>Heat dissipation</b>	910 Btu/h
<b>IP degree of protection</b>	IP20

## Communications & Management

<b>Alarm</b>	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
<b>Emergency power off</b>	Yes
<b>Control panel</b>	Multifunction LCD status and control console

## Surge Protection and Filtering

<b>Surge energy rate</b>	600 J
--------------------------	-------

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	24 cm
<b>Package 1 Width</b>	70 cm
<b>Package 1 Length</b>	54.5 cm
<b>Package 1 Weight</b>	13.7 kg

## Contractual warranty

<b>Warranty</b>	2 years repair or replace
-----------------	---------------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

RoHS Exemption Information [Yes](#)

## Certifications & Standards

**Eu RoHS Directive** Compliant  
[EU RoHS Declaration](#)

**China RoHS Regulation** [China RoHS declaration](#)  
Pro-active China RoHS declaration (out of China RoHS legal scope)

**Environmental Disclosure** [Product Environmental Profile](#)

**Weee** The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

**Circularity Profile** [End of Life Information](#)