

# Product datasheet

Specifications



## APC Easy UPS BVX 1200VA, 230V, AVR, India Sockets

BVX1200LI-IN

### Overview

Lead Time Usually in Stock

### Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Other Output Voltage	230 V
Rated Power In W	650 W
Rated Power In Va	1200 VA
Output Connection Type	6 India 3-pin 6A
Cable Length	1.22 m
Number Of Cables	1
Battery Type	Lead-acid battery
Provided Equipment	User manual

### Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Efficiency	<a href="#">View Efficiency Graph</a>
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	6 h
Battery Voltage	12 V
Battery Capacity	9 Ah
Extended Runtime	0

### General

Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No
Ups Size	WS

### Physical

Colour Black

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Height	19.0 cm
Width	14.0 cm
Depth	39.0 cm
Net Weight	7.5 kg
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

## Input

Network Frequency	40...70 Hz +/- 5 Hz auto-sensing
Plug Standard	India 3-pin 6A
Input Voltage Limits	140...300 V
Input Protection Type	Circuit breaker

## Output

Maximum Configurable Power In W	650 W
Output Frequency	50/60 Hz +/- 1 Hz unsynchronised
Ups Type	Line interactive
Wave Type	Stepped approximation to a sinewave
Graph Display	1
Maximum Configurable Power In Va	1200 VA
Transfer Time	6 ms typical : 10 ms maximum

## Conformance

Product Certifications	BIS
------------------------	-----

## Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 % non-condensing
Operating Altitude	0...3000 m
Ambient Air Temperature For Storage	-20...50 °C
Storage Relative Humidity	0...95 % non-condensing
Storage Altitude	0...15000 m
Acoustic Level	40 dBA
Ip Degree Of Protection	IP20

## Communications & Management

Control Panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

## Surge Protection and Filtering

---

Surge Energy Rate 255 J

## Packing Units

---

Unit Type Of Package 1 PCE

---

Number Of Units In Package 1 1

---

Package 1 Height 29.7 cm

---

Package 1 Width 49.5 cm

---

Package 1 Length 23.5 cm

---

Package 1 Weight 8.5 kg

## Contractual warranty

---

Warranty 2 Years on UPS & 1 Year on Battery

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

RoHS Exemption Information Yes

## Certifications & Standards

Reach Regulation	<a href="#">REACH Declaration</a>
Eu RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	<a href="#">End of Life Information</a>