

Product datasheet

Specifications



APC Easy UPS BVX 700VA, 230V, AVR, India Sockets

BVX700LI-IN

⚠ To be discontinued on: 30-Sept-2024

⚠ To be discontinued

Overview

Lead Time Usually in Stock

Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Other Output Voltage	230 V
Rated Power In W	360 W
Rated Power In Va	700 VA
Output Connection Type	3 India 3-pin 6A
Cable Length	1.22 m
Number Of Cables	1
Battery Type	Lead-acid battery
Provided Equipment	User manual

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	6 h
Battery Voltage	12 V
Battery Capacity	7 Ah
Extended Runtime	0

General

Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No
Ups Size	WS

Physical

Colour	Black
Height	13.8 cm
Width	9.8 cm
Depth	31.0 cm
Net Weight	4.2 kg
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No
Mounting Position	Vertical

Input

Network Frequency	40...70 Hz +/- 5 Hz auto-sensing
Plug Standard	India 3-pin 6A
Input Voltage Limits	140...300 V
Input Protection Type	Circuit breaker

Output

Maximum Configurable Power In W	360 W
Output Frequency	50/60 Hz +/- 1 Hz unsynchronised
Ups Type	Line interactive
Wave Type	Stepped approximation to a sinewave
Graph Display	1
Maximum Configurable Power In Va	700 VA
Transfer Time	6 ms typical : 12 ms maximum

Conformance

Product Certifications	BIS
------------------------	-----

Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 % non-condensing
Operating Altitude	0...3000 m
Ambient Air Temperature For Storage	-20...50 °C
Storage Relative Humidity	0...95 % non-condensing
Storage Altitude	0...15000 m
Acoustic Level	40 dBA
Ip Degree Of Protection	IP20

Communications & Management

Control Panel	LED status display with on line : on battery : replace battery and overload indicators
---------------	--

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
--------------	--

Surge Protection and Filtering

Surge Energy Rate	255 J
--------------------------	-------

Packing Units

Unit Type Of Package 1	PCE
-------------------------------	-----

Number Of Units In Package 1	1
-------------------------------------	---

Package 1 Height	22.2 cm
-------------------------	---------

Package 1 Width	14.2 cm
------------------------	---------

Package 1 Length	34.6 cm
-------------------------	---------

Package 1 Weight	4.7 kg
-------------------------	--------

Contractual warranty

Warranty	2 Years on UPS & 1 Year on Battery
-----------------	------------------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)



Transparency RoHS/REACH

Well-being performance

Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)

China Rohs Regulation

[China RoHS declaration](#)

Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure

[Product Environmental Profile](#)

Weee

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile

[End of Life Information](#)