

# Product datasheet

Specifications



## APC Back-UPS 1100VA, 230V, without auto shutdown software, 5 India outlets (1 surge)

BX1100C-IN

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Rated power in W	660 W
Rated power in VA	1100 VA
Nb of power socket outlets	4 India 2/3-pin 6A 1 India 2/3-pin 6A surge
Cable length	1.52 m
Number of cables	1
Battery type	Lead-acid battery

### General

Provided equipment	user manual
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

### Physical

Colour	Black
Height	28.2 cm
Width	13.2 cm
Depth	25.9 cm
Net weight	8.98 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

## Input

Network frequency	45...65 Hz auto-sensing
Plug standard	India 3-pin 6A
Input voltage limits	145...290 V
Switching current capacity	7 A

## Output

Maximum configurable power in W	660 W
Output frequency	50 Hz sync to mains
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Efficiency	72 % (full load) 84 % (half load)
Full load runtime	660 W
Maximum configurable power in VA	1100 VA
Transfer time	10 ms typical : 12 ms maximum

## Conformance

Product certifications	BIS
------------------------	-----

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...3000 m
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0...15000 m
Acoustic level	45 dBA

## Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	6 h
Number of battery replacement quantity	2
Battery voltage	24 V
Battery power in VAh	128 VAh runtime
Extended runtime	0

## Communications & Management

Control panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

## Surge Protection and Filtering

---

Surge energy rate	255 J
-------------------	-------

---

## Packing Units

---

Package 1 Weight	10.21 kg
------------------	----------

---

Package 1 Height	39.4 cm
------------------	---------

---

Package 1 width	20.3 cm
-----------------	---------

---

Package 1 Length	38.4 cm
------------------	---------

---

## Offer Sustainability

---

Sustainable offer status	Green Premium product
--------------------------	-----------------------

---

REACH Regulation	<a href="#">REACH Declaration</a>
------------------	-----------------------------------

---

EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
-------------------	--

---

Mercury free	Yes
--------------	-----

---

RoHS exemption information	<a href="#">Yes</a>
----------------------------	---------------------

---

Environmental Disclosure	<a href="#">Product Environmental Profile</a>
--------------------------	---

---

Circularity Profile	<a href="#">End of Life Information</a>
---------------------	---

---

Optimized Energy Efficiency	Energy efficient product
-----------------------------	--------------------------

---

Take-back	Take-back program available
-----------	-----------------------------

---

## Contractual warranty

---

Warranty	1 year repair or replace
----------	--------------------------

---