



## Overview

Lead time	Usually in Stock
-----------	------------------

## General

Provided equipment	User manual USB cable
Number of tare power	30 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

## Physical

Depth	54.4 cm
Height	43.2 cm
Mounting preference	No preference
Net weight	50.8 kg
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No
Width	19.6 cm

## Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug standard	India 3-pin 16A
Input voltage limits	151...302 V adjustable
Input voltage	230 V

## Output

Rated power in W	1980 W
Maximum configurable power in W	1980 W
Harmonic distortion	Less than 5 %
Output frequency	47...53 Hz for 50 Hz nominal sync to mains
UPS type	Line interactive
Wave type	Sine wave
Nb of power socket outlets	1 IEC 60320 C19 6 India 3-pin 6A
Efficiency	90 % (full load)
Output voltage	230 V
Maximum configurable power in VA	2200 VA
Rated power in VA	2200 VA
Transfer time	2 ms typical

## Conformance

Product certifications	BIS
------------------------	-----

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 m
Acoustic level	45 dBA
Heat dissipation	275 Btu/h

## Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Liquid value	0
Battery charger power	271 W rated
Battery power in VAh	816 VAh runtime
Battery life	2...4 year(s)
Extended runtime	0

## Communications & Management

Control panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

## Surge Protection and Filtering

Surge energy rate	365 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

## Packing Units

Package 1 Weight	64.86 kg
------------------	----------

Package 1 Height	70 cm
Package 1 width	38 cm
Package 1 Length	76 cm

### Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Under investigation
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

### Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------