

Technical Specifications

APC Easy UPS On-Line, 2000VA/1600W, Rackmount 2U, 230V, 4x IEC C13 outlets, Intelligent Card Slot, LCD, Extended runtime, No Battery, W/O rail kit | SRVPM2KRIL | Downloaded on 04/23/2024 (EST)



APC Easy UPS On-Line, 2000VA/1600W, Rackmount 2U, 230V, 4x IEC C13 outlets, Intelligent Card Slot, LCD, Extended runtime, No Battery, W/O rail kit

SRVPM2KRIL

Call for More Information

- High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.

| Output | |
|----------------------------------|--|
| Output power capacity | 1.6kWatts / 2.0kVA |
| Max Configurable Power (Watts) | 1.6kWatts / 2.0kVA |
| Nominal Output Voltage | 230V |
| Output Voltage Note | Configurable for 220 : 230 or 240 nominal output voltage |
| Efficiency at Full Load | 88.0 % |
| Output Voltage Distortion | 3 % |
| Output Frequency (sync to mains) | 50/60 Hz +/- 3 Hz Sync to mains |
| Other Output Voltages | 220 V, 240 V |
| Load Crest Factor | 3 : 1 |
| Topology | Double conversion online |
| Waveform type | Sine wave |
| Output Connections | (4) IEC 60320 C13 |
| Bypass | Internal bypass (automatic and manual) |

| Input | |
|---|---|
| Nominal Input Voltage | 230V |
| Input frequency | 40 - 70 Hz Auto sensing |
| Input Connections | IEC 60320 C14 |
| Input voltage range for main operations | 110 - 285 Half load, 160 - 280 Full loadV |
| Number of Power Cords | 1 |
| Efficiency at Full Load | 88.0 % |

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Easy UPS On-Line, 2000VA/1600W, Rackmount 2U, 230V, 4x IEC C13 outlets, Intelligent Card Slot, LCD, Extended runtime, No Battery, W/O rail kit | SRVPM2KRIL | Downloaded on 04/23/2024 (EST)

| Input | |
|----------------------|--------------|
| Other Input Voltages | 220 V, 240 V |

| Batteries & Runtime | |
|------------------------------|--|
| Battery type | External battery system |
| Nominal Battery Voltage | 72 V |
| Battery Charge Power (Watts) | 350 Watts |
| Efficiency | View Efficiency Graph (Available in Technical Tab on site) |

| Communications & Management | |
|-----------------------------|--|
| Control panel | Multifunction LCD status and control console |

| Surge Protection and Filtering | |
|--------------------------------|-----------|
| Surge energy rating | 600Joules |

| Physical | |
|-----------------|---------------|
| Maximum Height | 86MM, 8.6CM |
| Maximum Width | 438MM, 43.8CM |
| Maximum Depth | 462MM, 46.2CM |
| Rack Height | 2U |
| Net Weight | 9.2KG |
| Shipping weight | 13.4KG |
| Shipping Height | 240MM, 24.0CM |
| Shipping Width | 545MM, 54.5CM |
| Shipping Depth | 700MM, 70.0CM |
| Color | Black |

| Environmental | |
|-----------------------------|---------------------------|
| Operating Temperature | 0 - 40 °C |
| Operating Relative Humidity | 0 - 95 (Non-condensing) % |
| Operating Elevation | 0 - 3000meters |
| Storage Temperature | -20 - 50 °C |

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Easy UPS On-Line, 2000VA/1600W, Rackmount 2U, 230V, 4x IEC C13 outlets, Intelligent Card Slot, LCD, Extended runtime, No Battery, W/O rail kit | SRVPM2KRIL | Downloaded on 04/23/2024 (EST)

| Environmental | |
|---|---------------------------|
| Storage Relative Humidity | 0 - 95 (Non-condensing) % |
| Storage Elevation | 0 - 15000meters |
| Audible noise at 1 meter from surface of unit | 50.0dBA |
| Protection Class | IP20 |

| Conformance | |
|-------------------|---------------------------|
| Approvals | CE, EAC, TISI, UKCA |
| Standard warranty | 2 years repair or replace |

| Sustainable Offer Status | |
|--------------------------|-----------|
| RoHS | Compliant |

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.