

Technical Specifications

APC Easy UPS On-Line, 3kVA/2.4kW, Rackmount 2U, 230V, 6x IEC C13+1x IEC C19 outlets, Intelligent Slot, LCD, Extended runtime, No Battery, W/O rail kit | SRVPM3KRIL | Downloaded on 04/23/2024 (EST)



APC Easy UPS On-Line, 3kVA/2.4kW, Rackmount 2U, 230V, 6x IEC C13+1x IEC C19 outlets, Intelligent Slot, LCD, Extended runtime, No Battery, W/O rail kit

SRVPM3KRIL

Call for More Information

- High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.

Output	
Output power capacity	2.4kWatts / 3.0kVA
Max Configurable Power (Watts)	2.4kWatts / 3.0kVA
Nominal Output Voltage	230V
Efficiency at Full Load	88.0 %
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz Sync to mains
Other Output Voltages	220 V, 240 V
Load Crest Factor	3 : 1
Topology	Double conversion online
Waveform type	Sine wave
Output Connections	(1) IEC 60320 C19 (6) IEC 60320 C13
Bypass	Internal bypass (automatic and manual)

Input	
Nominal Input Voltage	230V
Input frequency	40 - 70 Hz Auto sensing
Input Connections	IEC 60320 C20
Input voltage range for main operations	110 - 285 Half load, 160 - 280 Full loadV
Number of Power Cords	1
Efficiency at Full Load	88.0 %
Other Input Voltages	220 V, 240 V

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Easy UPS On-Line, 3kVA/2.4kW, Rackmount 2U, 230V, 6x IEC C13+1x IEC C19 outlets, Intelligent Slot, LCD, Extended runtime, No Battery, W/O rail kit | SRVPM3KRIL | Downloaded on 04/23/2024 (EST)

Batteries & Runtime	
Battery type	External battery system
Nominal Battery Voltage	72 V
Battery Charge Power (Watts)	350 Watts
Efficiency	View Efficiency Graph (Available in Technical Tab on site)

Surge Protection and Filtering	
Surge energy rating	600Joules

Physical	
Maximum Height	86MM, 8.6CM
Maximum Width	438MM, 43.8CM
Maximum Depth	462MM, 46.2CM
Rack Height	2U
Net Weight	9.5KG
Shipping weight	13.7KG
Shipping Height	240MM, 24.0CM
Shipping Width	554MM, 55.4CM
Shipping Depth	700MM, 70.0CM
Color	Black

Environmental	
Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 (Non-condensing) %
Operating Elevation	0 - 3000meters
Storage Temperature	-20 - 50 °C
Storage Relative Humidity	0 - 95 (Non-condensing) %
Storage Elevation	0 - 15000meters
Audible noise at 1 meter from surface of unit	50.0dBA

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Easy UPS On-Line, 3kVA/2.4kW, Rackmount 2U, 230V, 6x IEC C13+1x IEC C19 outlets, Intelligent Slot, LCD, Extended runtime, No Battery, W/O rail kit | SRVPM3KRIL | Downloaded on 04/23/2024 (EST)

Conformance	
Approvals	CE, EAC, TISI, UKCA
Standard warranty	2 years repair or replace

Sustainable Offer Status	
RoHS	Compliant

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.