



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	Smart UPS signalling RS-232 cable User manual Warranty card
--------------------	---

Physical

Cable length	1.52 m
Colour	Black
Depth	40 cm
Height	22 cm
Net weight	5.7 kg
Width	14.5 cm

Input

Network frequency	40...70 Hz
Plug standard	India 3-pin 6A
Input voltage limits	110...280 V half load
Switching current capacity	10 A
Input voltage	230 V

Output

Rated power in W	800 W
Maximum configurable power in W	800 W
Harmonic distortion	Less than 2 %
Output frequency	50/60 Hz +/- 3 Hz sync to mains

Outputvoltage_other	220 V 240 V
Crest factor	3 : 1
UPS type	Double conversion online
Wave type	Sine wave
Nb of power socket outlets	4 India 3-pin 6A
Output voltage	230 V

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...3000 ft
Ambient air temperature for storage	-20...60 °C
Storage altitude	0.00...4572.00 m

Batteries & Runtime

Battery type	External battery system
Number of battery filled slots	0
Number of battery free slots	0
Liquid value	0

Communications & Management

Control panel	LED status display with load and battery bar-graphs and on line : on battery : replace battery : and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Packing Units

Package 1 Weight	6.3 kg
Package 1 Height	34 cm
Package 1 width	23.5 cm
Package 1 Length	47.8 cm
Number of Units in Package 3	60
Package 3 Weight	398 kg
Package 3 Height	216.6 cm
Package 3 width	100 cm
Package 3 Length	120 cm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------